



**CX480100**  
**Full surface induction cooktop**  
**Frameless**  
**Width 80 cm**

**One single big cooking surface**  
**Free positioning of cookware**  
**All sizes and formats of cookware can be used**  
**TFT touch display for an intuitive control of all functions**  
**Max. power output for big cookware of up to 4.4 kW**  
**Frameless for flush installation**

**Cooking zones**  
One unique cooking surface of 2800 cm<sup>2</sup>.  
Up to 4 items of cookware can be placed simultaneously on the cooktop.

**Handling**  
Easy to use colour graphic TFT touch display with use indications.  
Electronic power control in 17 output levels.

**Features**  
Booster function.  
Timer for each cooking position.  
Short-term timer.  
Information key with use indications.  
Power management.

**Safety**  
Main switch.  
Individual pot detection.  
Residual heat indicator.  
Child lock.  
Display cleaning protection.

**Planning notes**  
Operates with magnetic (induction) iron pots and pans only. For an optimal heat distribution, the use of sandwich bottom cookware is recommended. The wok pan WP 400 001 cannot be used with this appliance.  
Immersion depth 64.6 mm.  
Intermediate shelf is required.  
Appliance must be fixed from underneath.  
Cooktop clamping range: 30 - 50 mm.  
Joint width may vary due to dimensional tolerances of the glass ceramic cooktop and the worktop cut-out.

**Connection**  
Total connected load 7.2 kW.  
Connecting cable 1.5 m without plug.

**Characteristics**  
**Product name/family**  
Cooking zone ceramic  
**Construction type**  
Built-in  
**Energy input**  
Electric  
**Total number of positions that can be used at the same time**  
4  
**Type of control setting devices**  
Touchscreen  
**Required niche size for installation (HxWxD)**  
64.6 x 780-798 x 518-490  
**Width of the product (mm)**  
793  
**Dimensions of the product (mm)**  
64.6 x 793 x 513  
**Net weight (kg)**  
26.000  
**Gross weight (kg)**  
28.000  
**Residual heat indicator**  
**Location of control panel**  
Hob front  
**Type of external control possibility**  
Basic surface material  
**Color of surface**  
anthracite  
**Color of frame**  
**Approval certificates**  
AENOR, CE  
**Length electrical supply cord (m)**  
150.0

**Consumption and connection features**  
**Electrical connection rating (W)**  
7200  
**Gas connection rating (W)**  
**Current (A)**  
**Voltage (V)**  
220-240  
**Frequency (Hz)**  
60; 50

created on 2014-05-13  
Page 1

**Color Variants**

**CX480100**  
**Frameless**  
**Width 80 cm**

**Optional accessories**

**GN232110**  
**Teppan Yaki made of multi ply material,**  
**GN232230**  
**Teppan Yaki made of multi ply material,**

